



HF Inlays & Tags

Product Range

With a wide selection of antenna choices and protocols, our HF tags and inlays offer great application flexibility and fit-for-function design in the most demanding applications.

HF 13.56 MHz ISO-compliant RFID technology is a proven, globally accepted solution for a vast array of markets. The technology is a perfect fit for item-level authentication and asset tracking solutions in pharmaceutical and medical applications. Popular industry applications consist of library and rental item level tagging for automated self checkout and return of printed and digital media, as well as industrial closed loop systems for manufacturing automation.

RFID can also be utilized as personal currency in ticketing and customer loyalty card applications.

HF RFID technology offers proven robust performance with short-to-medium read ranges even when used around difficult materials such as liquids and metals.

Smartrac's operations are certified to the ISO 9001:2015 Quality Management System standards and the ISO 14001:2015 Environmental Management System standards.

Overview

Operating Frequency

13.56 MHz

International Standards











- ▶ ISO 14443 A
- ▶ ISO 15693
- ▶ ISO 18000-3 Mode 1
- ▶ ISO 18000-3 Mode 3

Application Areas

- ▶ Healthcare
- ▶ Media & Document Management
- ▶ Product Authentication
- ▶ ... and many more

HF Inlays & Tags

Product Range (selection)

Product	Product Name	Protocol	IC	Antenna & Die-cut Size
	MINIBLOCK	ISO 15693 ISO 18000-3 Mode 1	NXP ICODE SLIX family NXP ICODE SLIX2 family	14.5 × 14.5 mm / 0.6 × 0.6" 18 × 18 mm / 0.7 × 0.7"
	MICROTRACK	ISO 15693 ISO 18000-3 Mode 1	NXP ICODE SLIX family Infineon my-d vicinity 2k Infineon my-d vicinity 10k	20 × 10 mm / 0.79 × 0.39" 22 × 12 mm / 0.87 × 0.47"
	MINITRACK	ISO 15693 ISO 18000-3 Mode 1	NXP ICODE SLIX family NXP ICODE SLIX2 family	14 × 31 mm / 0.6 × 1.2" 18 × 36 mm / 0.7 × 1.4"
	MINITRACK	ISO 14443 A	NXP MIFARE family Classic & Ultralight NXP ICODE SLIX & SLIX2	22.5 × 38.0 mm / 0.89 × 1.50"
	BLOCK LITE	ISO 15693 ISO 18000-3 Mode 1	NXP ICODE SLIX family NXP ICODE SLIX2 family	47 × 47 mm / 1.9 × 1.9" 50 × 50 mm / 2.0 × 2.0"
	BLOCK	ISO 18000-3 Mode 3	NXP ICODE ILT-M family	45 × 45 mm / 1.77 × 1.77" 48 × 48 mm / 1.89 × 1.89"
	RACETRACK LITE	ISO 15693 ISO 18000-3 Mode 1	NXP ICODE SLIX family NXP ICODE SLIX2 family	45 × 76 mm / 1.8 × 3.0" 49 × 81 mm / 1.9 × 3.2"
	CIRCUS™	ISO 15693 ISO 18000-3 Mode 1	NXP ICODE SLIX family NXP ICODE SLIX2 family	∅ 18 mm / 0.7" ∅ 21 mm / 0.8"
	BULLSEYE™	ISO 15693 ISO 18000-3 Mode 1	NXP ICODE SLIX family NXP ICODE SLIX2 family	∅ 33 mm / 1.3" ∅ 40 mm / 1.6"
	STINGRAY	ISO 15693 ISO 18000-3 Mode 1	NXP ICODE SLIX family NXP ICODE SLIX2 family	∅ 105 mm / 4.1" ∅ 108 mm / 4.3"

Additional memory, protocol and product configurations are available upon request. Note: Pictures are for illustration only and are not to scale.
*Chip position varies in the different antenna designs.

IC Total Memories

- ▶ NXP ICODE SLIX 1k bit
- ▶ NXP ICODE SLIX2 2.5k bit
- ▶ NXP ICODE ILT-M 240 bit EPC + 5 12 bit
- ▶ NXP MIFARE Ultralight 64 byte - 192 byte
- ▶ NXP MIFARE Classic 1k 1024 byte
- ▶ Infineon my-d vicinity 2k 244 byte
- ▶ Infineon my-d vicinity 10k 992 byte

Smartrac N.V. · Strawinskyalaan 851 · 1077 XX Amsterdam · The Netherlands

Phone: +31 20 30 50 150 · Fax: +31 20 30 50 155

Contact: Sales & Customer Service

smartrac-group.com/contact

© 2018 Smartrac N.V.

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use.

info@smartrac-group.com

